


1.0' 0"




SECTION THROUGH THE
WALL WITH THE 1' 0" OF THE
STITCHED JOIST

NINJA T



UNITO 2.0



SECTION V: KUSARI FUNDO CONSTRUCTION

A length of chain or rope with two weighted ends is swung and strikes with the *Kusari Fundo*, sometimes called a *Shimadagumi*, which consists of all weapons together. Essentially it is made out of chain and metal and weights, but as illustrated in Diagram 1, a section of the weapon can also be made from two thick large rounded wooden ends just as wide as length of rope, wire, or spring steel and with heavy brass or iron ends for the end weights. Inexpensive sample: the *Kusari Fundo* is one of the most deadly weapons in the State arsenal. A length of chain or rope with weighted ends is held in one hand while other weapon is held, striking the drops and the *Kusari Fundo*. See Photo 1 for a picture of a decorated *Kusari Fundo*, and Photo 2 for a State arming *Kusari Fundo*.



Photo 1.1

Use of a Construction Rope

1. First determine length of chain or rope, usually 17' long.
2. Fasten one end of metal rings (standard size 1-1/2" or 1-3/4" diameter) distributed in the metal weight to replace those removed and the same gripping (thick rounded ends in chain large and heavy ones).
3. Second end weight is made out of the chain and permits making chain serve also as metal chain and weights to each end of the rope by using the rope in the bag, and the bag in the rope.
4. First is somewhat optional.



Diagram 1.1



2. The blade is attached to the handle with a pin and nut, and the handle is secured with a screw.



blade edge



1/2" blade
1/2" pin and nut
1/2" handle



blade edge



blade edge

BLADE-TO-HANDLE CONSTRUCTION 8.2

SECTION VI: NINJA KUSARI GAMA CONSTRUCTION

Table 1: Construction Steps

1. Measure blade.
2. Measure handle and cut accordingly.
3. Mount blade into handle about handle.
4. Attach ring clamps as shown in Diagram 1.

5. Drill one hole through handle vertically.
6. Attach pins and secure with glue.
7. Measure rings at about end of handle.
8. Attach the other end of the 2 rings to handle in the middle of the handle with a couple glue for 2 rings to hold.
9. Paint in camouflage optional.

The Kusari Gama is a unique blade used in the weapon. The blade portion has a straight blade (shown in Diagram 1). Refer to the attached images on the back of Diagram 1. Measure handle (about 10 in) and cut accordingly. Mount blade into handle and secure with wood glue. Add rings as shown in Diagram 1. A finished Kusari Gama is shown in Photo 1. A close-up of the Kusari Gama is shown in Photo 2.



Photo 1: Kusari Gama



Photo 2: Kusari Gama

KUBARI-GAMA BLADE PATTERNS 0.1



NINJA PUNYA: BLOWGUN & DARTS 3.0





REPORT

